

TP-2000

STATIONARY COMPACTOR SPECIFICATIONS

A. Manufactured

1. To meet American National Standard Institute specifications Z245.2-1997.
2. Total UL Approval on entire unit.

B. Rating

1. 2 Yard Chargebox

C. Dimensional Information

1. Overall Height 48"
2. Overall Width 81 1/2"
3. Overall Length 130"
4. Ram Force Normal Force 48,000 lbs. Maximum Force ... 57,500 lbs.

E. Chargebox

1. Chargebox opening 40" Long x 60" Wide
2. Formed one piece chargebox eliminating mis-fitted joints and providing a uniform fit
3. Heavy Duty Gauge Steel Construction with steel channel reinforced sidewalls and floor for increased strength.

F. Cylinder

1. (1) 6" diameter x 3.5" rod x 56" stroke industrial grade cylinder.

G. Power Unit

1. 10 HP Motor supplied standardly in tri-voltage, three phase.
2. Internal Power Unit

H. Control Panel

1. Push Button Control Station on 13' of Sealtite which consists of keyed ON/OFF power switch, START/REVERSE switch, Full Container Light and EMERGENCY STOP Button.

I. Warranty

1. Two full years on defective parts & labor warranty.
2. Three years on major components (Cylinder, Motor, Pump).

J. Service and Parts

1. Factory authorized parts and service organization with 1-800 24-hour customer service hotline.

K. Finish

1. High quality industrial enamel paint from standard color chart.