

# TP2000HD

## STATIONARY COMPACTOR SPECIFICATIONS

### A. Manufactured

1. To meet American National Standard Institute Specifications Z245.2-1997.
2. Total UL Approval on entire unit.

### B. Rating

1. 2 Yard Chargebox.

### C. Dimensional Information

1. Overall Height .... 48"
2. Overall Width .... 81½"
3. Overall Length .... 130"
4. Compactor weight 4,800 lbs.

### D. Structure/Frame

1. Heavy Duty 1/4" Gauge Steel Construction.
2. Certified Weld Construction by Certified AWS Category I & II Craftsmen.
3. Standard Retainer Teeth.
4. Ram Force  
Normal Force .... 59,000 lbs.  
Maximum Force ... 70,000 lbs.

### E. Chargebox

1. Chargebox Opening 40" Long x 60" Wide
2. Formed one piece chargebox eliminating mis-fitting joints and providing uniform fit.
3. Heavy Duty 1/4" Gauge Steel Construction with steel channel reinforced side walls and floor for increased strength.
4. Ram body ¼" one piece form to fit form of compactor body for strength

### F. Cylinder

1. (1) 6" diameter x 3.5" rod x 56" stroke industrial grade cylinder.

**G. Power Unit**

1. 15 HP Motor supplied standard in tri-voltage, three phase.
2. Internal Power Unit

**H. Control Panel**

1. Push Button Control Station on 13' of Sealtite which consists of keyed ON/OFF power switch, START/REVERSE switch, Full Container Light and EMERGENCY STOP Button.

**I. Warranty**

1. One full year on defective parts & labor warranty.

**J. Service and Parts**

1. Factory authorized parts and service organization with 1-800 24 hour customer service hotline.

**K. Finish**

1. High quality industrial enamel paint from standard color chart.