

**PTR**

800-523-3654

**BALER & COMPACTOR**

www.ptrco.com

**Self-Contained Compactors**

Totally



Listed!

**PT-200**

(20 Cubic Yards)



The PT-200 Compactor has been engineered and manufactured to provide many years of reliable service. The heavy-duty structural steel components are welded by AWS certified technicians and water tested to ensure leak proof containment under high compaction forces. This unit has total U.L. approval, standard 3 button controls, On/Off key switch, mushroom stop, auto reverse and a *Sure-Tite*™ door seal.

**Specifications**

Charge Box Capacity	1 Cu Yd
Container Capacity	20 Cu Yd
Clear Top Opening (L x W)	31" x 50"

**Electrical Equipment**

Electrical Motor 208/230/460v	3 Phase
Horse Power	5
Electrical Control Voltage	120 VAC

**Performance Characteristics**

Cycle Time	45 sec
Total Normal Force	39,611 lbs
Total Maximum Force	52,287 lbs
Normal Ram Face Pressure	39.8 psi
Maximum Ram Face Pressure	52.6 psi

**Hydraulic Equipment**

Hydraulic Pump Capacity	6.5 gpm
Normal Pressure	1750 psi
Maximum Pressure	2400 psi
Hydraulic Cylinder (2) Bore	4"
Hydraulic Cylinder Rod	2.5"



PTR Baler & Compactor Company • 2207 E Ontario St. • Philadelphia, PA 19134  
215-533-5100 • (FAX) 215-533-8907 • 800-523-3654 • www.PTRCO.com



Printed in the U.S.A.  
©PTR Baler & Compactor